

# 260



## Overhead sprinklers

### Metal impact sprinkler | 1/4" female

**Applications:** permanent and supplementary irrigation of sugarcane, maize, cotton and pasture.

- High water distribution with spacing up to 27 m
- Slow rotation at uniform speed
- Recommended working pressure: 2.0 – 4.0bar
- Lightweight and easy to handle
- Adjustable diffuser screws allows stream breakage at low pressure conditions.
- Non-clog straightening vane to ensure excellent coverage in windy conditions

**260, 260PC** PERFORMANCE TABLE

| Nozzle color (mm) | P (bar) | Q (m <sup>3</sup> /h) | D (m) |
|-------------------|---------|-----------------------|-------|
| 8.0               | 1.5     | 2.9                   | 31    |
|                   | 2.0     | 3.4                   | 34    |
|                   | 3.0     | 4.1                   | 38    |
|                   | 4.0     | 4.8                   | 41    |
| 9.0*              | 1.5     | 3.7                   | 33    |
|                   | 2.0     | 4.2                   | 35    |
|                   | 3.0     | 5.2                   | 39    |
|                   | 4.0     | 6.0                   | 42    |
| 10.0              | 1.5     | 4.5                   | 34    |
|                   | 2.0     | 5.3                   | 36    |
|                   | 3.0     | 6.4                   | 41    |
|                   | 4.0     | 7.4                   | 44    |
| 12.0              | 1.5     | 6.6                   | 34    |
|                   | 2.0     | 7.6                   | 38    |
|                   | 3.0     | 9.3                   | 42    |
|                   | 4.0     | 10.7                  | 47    |

\*Standard nozzle

\* Performance table prepared under laboratory conditions

\* For windy conditions use closer spacing

# 260 PC



## Overhead sprinklers

### Full and part circle metal impact sprinkler | 1/4" female

Specifically designed for irrigation of field edges

