

1" SPRINKLER 5035 G



Overhead sprinklers

Plastic impact sprinkler 1" female

Applications: general field use with solid-set irrigation systems

- High water distribution with spacing up to 22m
- Color-coded bayonet nozzle for easy service
- Integrated stream-straightening vane for maximum range
- High-impact, heavy-duty plastic materials provide resistance to corrosion, chemicals and UV radiation

5035-G-1" PERFORMANCE TABLE

Precipitation rates (mm/hr) and uniformity (CU) at various spacing

Nozzle color (mm)	P (bar)	Q (m ³ /h)	D (m)	Spacing (m)			
				12x18	18x18	20x20	22x22
6.5x2.5L Grey	3.0	3.070	34.0	14.2	9.5	7.7	6.2
	4.0	3.550	36.5	16.4	11.0	8.9	7.1
	5.0	3.970	37.0	18.4	12.3	9.9	8.0
6.5x3.2 Grey	3.0	3.200	35.0	14.8	9.9	8.0	6.6
	4.0	3.700	37.0	17.1	11.4	9.3	7.6
	5.0	4.150	36.0	19.2	12.8	10.4	8.6
7.0x2.5L Green	3.0	3.450	35.0	16.0	10.6	8.6	7.0
	4.0	3.970	38.5	18.4	12.3	9.9	8.1
	5.0	4.390	37.0	20.3	13.5	11.0	9.0
7.0x3.2 Green	3.0	3.550	35.0	16.4	11.0	8.9	7.3
	4.0	4.100	37.0	19.0	12.7	10.3	8.5
	5.0	4.600	35.0	21.3	14.2	11.5	9.5

*Standard nozzle

Rear nozzle color : 2.5L - grey; 3.2 mm - orange

Color code - Distribution uniformity	CU > 92%	CU 88-92%	CU 85-88%	CU < 85%
--------------------------------------	----------	-----------	-----------	----------

* Performance table prepared under laboratory conditions

* For windy conditions use closer spacing

1" SPRINKLER 234



Overhead sprinklers

Metal impact sprinkler 1" female

Applications: all overhead irrigation of crops with solid-set, mechanized or hand-line systems.

- High water distribution with spacing up to 24 m.
- Color-coded bayonet nozzles for easy service.
- Integrated stream-straightening vane for maximum range.
- Sand, and dust protection sleeve ensures reliable operation and durability.
- Red-cap completely seals and protects the drive spring and protects from frost damage.

234 PERFORMANCE TABLE

Precipitation rates (mm/hr) and uniformity (CU) at various spacing

Nozzles color mm	P (bar)	Q (m ³ /h)	D (m)	Spacing (m)			
				18x18	20x20	20x24	24x24
5.0x3.2 Purple	3.0	2.210	32	6.8	5.5		
	4.0	2.530	34	7.9	6.4		
	5.0	2.840	35	8.8	7.2		
5.5x3.2 Orange	3.0	2.500	34	7.7	6.2	5.2	4.3
	4.0	2.900	37	8.9	7.2	6.0	5.0
	5.0	3.250	39	10.0	8.1	6.8	5.6
6.0x3.2 Red	3.0	2.810	37	8.8	7.1	5.9	4.9
	4.0	3.300	37	10.1	8.2	6.8	5.7
	5.0	3.700	40	11.3	9.1	7.6	6.3
6.5x3.2 Grey	3.0	3.200	37	9.9	8.0	30.5	5.6
	4.0	3.700	37	11.4	9.3	35.2	6.4
	5.0	4.150	40	12.8	10.4	39.5	7.2
7.0x3.2 Green	3.0	3.550	38	11.0	8.9	7.4	6.2
	4.0	4.100	41	12.7	10.3	8.5	7.1
	5.0	4.600	43	14.2	11.5	9.6	8.0

Rear nozzle color : 3.2mm - orange

Color code - Distribution uniformity	CU > 92%	CU 88-92%	CU 85-88%	CU < 85%
--------------------------------------	----------	-----------	-----------	----------

* Performance table prepared under laboratory conditions

* For windy conditions use closer spacing